



PR-7120

High-speed thermal receipt printer

Front paper loading

2"/3" paper roll compatible

Print speed up to 250 mm/s

Low-noise operation

Status indicators

Windows/Linux/OPOS/JPOS driver

3-in-1 interface: USB, Serial, Ethernet

Model Number PR-7120

Printing Parameter

Print Method	Direct thermal line printing
Print Buffer	48K byte
Printing Speed	260mm/sec (MAX)
Dot Density	203 dpi
Printing Width	72 mm
Printing Direction	Unidirectional with friction feed

Character

Character Set	Multilingual x 12, Chinese, Japanese, Thai, Others
Character/columns	Font A(12×24) 48 columns / Font B(9×17) 64 columns / Chinese (24×24) 24

Command

Emulation	ESC/POS command compatible
-----------	----------------------------

Detection

Sensor	Paper out detection, Cover open detection
--------	---

Interface

Interfaces	Serial / USB / Ethernet 3 in 1 interface
------------	--

Cash Drawer Kick-Out	1 port
----------------------	--------

Reliability

Thermal Head	150km, 2 million cuts
--------------	-----------------------

Cutter

Type	Guillotine
Cutting Method	Full/partial cut

Power

Input	AC 100V - 240V
Output	24VDC /2.5A

Mechanical

Dimensions (L×W×H)	137.3×132×134 mm
Weight	1.33 kg
Color	Black/White

Environment

Operating Temperature	0 ~ 50°C
Storage Temperature	-20 ~ 70°C
Certifications	CE/FCC
Operating System Compatibility	Windows 2000/XP/Vista/Win7/Win8/Win10/POSReady 7/Linux CUPS/OPOS/ JavaPOS driver compatible